

Stay pumped - all along the journey.

Spare parts for the ContiMobilityKit:
the tyre sealant.

- › Replacement product of original equipment quality
“Engineered in Germany”
- › Extended shelf life up to 5 years
- › No need to remove and replace valve core



Extended movability even in case of a puncture.

The tyre sealant is pumped by the Continental compressor into the tyre, enabling the onward journey to the nearest garage or tyre service (max. 80 km/h and max. 200 km). It seals car tyre punctures caused by nails or similar objects with a diameter of up to 6 mm.

Product contents:

- › Pressure-resistant 450 ml tyre sealant bottle

Technical specifications of sealant bottle:

Sealant amount	Shelf life	Dimensions
450 ml	5 years	Ø 87 mm x 125 mm
Weight	Application temperature	
585 g	-30° C to +60° C	

Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi). 450 ml Replacement bottles can be used as a replacement for ContiMobilityKit's 300 ml, 450 ml and 560 ml OE bottles (560 ml OE bottle depending on tyre dimensions - please see chart).

Tyre width in mm	Tyre cross section												Rim size in inches
130 195	25 - 80												R 10 R 14
135/	25	30	35	40	45	50	55	60	65	70	75	80	R 15
145/	25	30	35	40	45	50	55	60	65	70	75	80	
155/	25	30	35	40	45	50	55	60	65	70	75	80	
165/	25	30	35	40	45	50	55	60	65	70	75	80	
175/	25	30	35	40	45	50	55	60	65	70	75	80	
185/	25	30	35	40	45	50	55	60	65	70	75	80	
195/	25	30	35	40	45	50	55	60	65	70	75	80	
205/	25	30	35	40	45	50	55	60	65	70	75		
215/	25	30	35	40	45	50	55	60	65	70			
225/	25	30	35	40	45	50	55	60	65				
235/	25	30	35	40	45	50	55	60					
245/	25	30	35	40	45	50	55						
155/	25	30	35	40	45	50	55	60	65	70	75	80	
165/	25	30	35	40	45	50	55	60	65	70	75	80	
175/	25	30	35	40	45	50	55	60	65	70	75	80	
185/	25	30	35	40	45	50	55	60	65	70	75	80	
195/	25	30	35	40	45	50	55	60	65	70	75	80	
205/	25	30	35	40	45	50	55	60	65	70			
215/	25	30	35	40	45	50	55	60	65				
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50	55						
245/	25	30	35	40	45	50							
185/	25	30	35	40	45	50	55	60	65	70	75		
195/	25	30	35	40	45	50	55	60	65	70			
205/	25	30	35	40	45	50	55	60	65				
215/	25	30	35	40	45	50	55	60	65				
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50	55						
245/	25	30	35	40	45	50							
255/	25	30	35	40	45								
265/	25	30	35	40									
275/	25	30	35										
285/	25	30	35										
285/	25	30	35										

Tyre width in mm	Tyre cross section												Rim size in inches
205/	25	30	35	40	45	50	55	60					R 18
215/	25	30	35	40	45	50	55	60					
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50							
245/	25	30	35	40	45								
255/	25	30	35	40	45								
265/	25	30	35	40									
275/	25	30	35										
285/	25	30	35										
295/	25	30											
215/	25	30	35	40	45	50	55						
225/	25	30	35	40	45	50	55						
235/	25	30	35	40	45	50							
245/	25	30	35	40	45								
255/	25	30	35	40									
265/	25	30	35										
275/	25	30	35										
225/	25	30	35	40	45								
235/	25	30	35	40	45								
245/	25	30	35	40									
255/	25	30	35										
265/	25	30	35	40	45								
275/	25	30	35	40	45								
285/	25	30	35										
265/	25	30	35										